Index Plungers Compact • with hexagon collar 22110.0244



Product Description

Index plungers are used for indexing bores.

Types with / without lock have the same building height.

Due to a thread recess the index plungers can be completely screwed in.

Material

Body

Stainless steel 1.4305

Locking pin

· Stainless steel 1.4305, nickel-plated

Assembly

The screw length can be adapted by distance collars for index plungers (EH 22120.).

More information


Notes

Knob not removable. Lock nuts have to be purchased separately.

Further products

- · Mounting Blocks, for index bolts and index plungers, die-cast Locating Bushings, for index bolts and index
- plungers
- Distance Collars, for index plungers

Drawing



0

Order information


	Dimensions								ws	Spring load ¹⁾		ß	Ĭ	Art. No.
d ₁ -0.02 -0.05	d ₂	l₂ min.	d₄	d ₅	I ₃	I4	I ₅	I ₆		F ₁ ~	F2 ~	max.		
[mm]									[mm]		[N]	[°C]	[g]	
without	without knob – picture 2, Stainless steel													
4	M8 x 1	6	М3	7	16	5	4.5	2.5	10	4	12.5	250	9	22110.0244

1) statistical average value

Accessories

Lock nuts ISO 8675 (DIN	Dimensions d ₂ [mm] 439), Stainless steel	Wrench size [mm]	a [9]	Art. No.
	M8x 1	13	2.7	22120.0514

Application example



Compliance

RoHS compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.

