Mounting Pads • protected against slipping

22590 1106



Product Description

Mounting pads can be used as foot or thrust pad. Not parallel bearing surfaces up to 15° degrees can be compensated.

The plastic cover on the mounting pad prevents slipping.

Material

Ball element

· Stainless steel 1.4305

Rubber cap

· Rubber, black

Pad


· Thermoplastic POM, white


More information

Notes

For the versions d_1 = M10 and M12 the lock nut conforms to DIN 934.

Drawing





Order information

d₁	d ₂	Dimensions h ₁	h ₂	t	ws	Load capacity for static load max.	ă	Art. No.
[mm]					[mm]	[kN]	[9]	
pad from thermoplastic, ball element from stainless steel – picture 1, Thermoplastic								
М6	22.5	16.5	6.4	5	10	4	7.8	22590.1106

Compliance

RoHS compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Halder France SAS www.halder.fr Page 1 of 1

Published on: 4.2.2024