# **Pins**

# 22690.0423



## **Product Description**

To be used as seats, stops and thrust pads.

#### **Material**


• Steel, case-hardened, blackened

### More information


### **Further products**

- · Seating Pins, ribbed or pointed
- Pins, with plastic bearing surface


## **Drawing**









picture 2




picture 3







picture 5




# **Order information**

Dimensions					ws	Tightening	I	Art. No.
<b>h</b> ±0.1	d <sub>1</sub>	d <sub>2</sub>	I	t		torque <sup>1)</sup> max.	_	
[mm]					[mm]	[Nm]	[9]	
with female thread, bearing surface spherical – picture 5								
25	M8	19.4	25	12	17	25	41	22690.0423

<sup>1)</sup> The tightening torque of bolts with female thread is for threaded pins, quality 8. The bolt has to be tightened over the total thread length.

www.halder.fr Page 1 of 2 Published on: 11.8.2024

## **Application example**



## Compliance

### **RoHS** compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

### Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 27.06.2024.

### **Contains Proposition 65 substances**



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.

www.halder.fr



Page 2 of 2 Published on: 11.8.2024