# Self-Aligning Pads 22730.0113



## **Product Description**

Self-aligning pads are used as stop, support and thrust pad and are suitable for installation in clamping elements.

### **Material**

### Ball

• Stainless steel 1.3541, nickel-plated

#### Body


• Stainless steel 1.4057, heat-treated


## More information


## Notes

Ball protected against rotating. Loading capacity valid for steel and stainless steel designs.

## Drawing








# picture 4

l<sub>1</sub> ± 0,1

## Order information

Dimensions						WS	Load capacity	Tightening		Art. No.
d1	d <sub>2</sub>	d <sub>3</sub>	I <sub>1</sub>	<b>I₂</b> -0.5	Ball diameter		for static load max.	torque max.	_	
[mm]						[mm]	[kN]	[Nm]	[g]	
with male thread, flat-faced ball, bearing surface plain – picture 1, Stainless steel										
13	M8	7.2	13	8	10	11	10	25	13	22730.0113

## **Application example**



# Compliance

### **RoHS compliant**

Compliant according to Directive 2011/65/EU and Directive 2015/863.

### Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

### Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

### Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.