# Self-Aligning Pads ⋅ adjustable 22740.0030



# **Product Description**

Self-aligning pads are used as stop, support and thrust pad and are suitable for installation in clamping elements.

#### **Material**

#### Ball

· Ball-bearing steel, hardened, bright

· Heat-treated steel, tempered, phosphated


• Steel, blackened (ISO 4035)

# More information

#### Notes

Ball protected against rotating. Loading capacity valid for steel and stainless steel designs. Special types on request.

# **Drawing**




#### **Order information**

Dimensions						Load capacity	Tightening torque	I	Art. No.
d <sub>1</sub>	I	I <sub>1</sub>	d <sub>2</sub>	е	Ball diameter	for static load max.	max.	_	
		 [mi	 m]		[kN]	[Nm]	[9]		
with flat-faced ball, bearing surface plain – picture 1, Heat-treated steel									
M20	77.3	50	20	33	25	90	407	277	22740.0030



Halder France SAS www.halder.fr Page 1 of 2

# **Application example**



# Compliance

# **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

#### Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

Halder France SAS

#### Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

# **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halder.fr Page 2 of 2

Published on: 4.2.2024