Adjustable Clamping Levers • with axial bearing, with female thread 24420.0110



Product Description

Adjustable clamping levers find versatile applications when the area of use is confined or a specific lever position is required.

- Advantages of axial bearing:
- Double clamping force with same lever size, by reducing the surface friction.
- · Protection of workpiece by a fixed locating surface.
- · Little setting due to higher pre-clamping force of bolt, e.g. thread.

Material

Lever

· Zinc die-cast, plastic coated, orange similar to RAL 2004, matt structure

Threaded part

· Steel, nitrided, blackened

Inner parts


· Steel, nitrided, blackened

Operation

serration

By lifting the lever the serrations are disengaged. The lever can be positioned by the serrations. On releasing the lever, the serrations are automatically re-engaged.

Drawing



Order information

Dimensions									I	Art. No.
d ₁	d2	d ₃	h ₁	h ₂	h ₃	l ₂	t₁ min.	t ₂	_	
[mm]									[g]	
orange										
22	M8	25	39.5	56	3.5	74	14	4.2	138	24420.0110

Application example

Increase of clamping force with axial bearing (while manual force is unchanged) Clamping force F Axial bearing M = const.

Compliance

RoHS compliant Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w Contains lead - SVHC list [REACH] as of 23.01.2024.

Contains Proposition 65 substances

Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.

