# **Adjustable Tension Levers**

24440.0326



# **Product Description**

## **Material**

### Lever

· Steel, blackened

## Inner parts

• Steel, blackened, quality 5.8

#### Screw

· Steel, blackened, quality 5.8

### Ball knob

• Thermosetting plastic PF 31, black, DIN 319

# **Operation**


By lifting the lever the serrations are disengaged. The lever can be positioned by the serrations. On releasing the lever, the serrations are automatically re-engaged.


### More information


#### **Notes**

The threaded portion can be exchanged.

# **Drawing**







# Order information

Dimensions										I	Art. No.
d <sub>1</sub>	d <sub>2</sub>	I <sub>1</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	l ~	_	
[mm]											
with screw – picture 2, Steel											
28	M12	40	19	12	30	48.5	4.5	4.5	110	298	24440.0326

# Compliance

# RoHS compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

## Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 23.01.2024.

## **Contains Proposition 65 substances**



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Halder France SAS

www.halder.fr