# **Knurled Nuts •** DIN 6303

# 24480.0310



# **Product Description**

#### **Material**

• Stainless steel 1.4305

#### **Assembly**


Form B: after being bored through the pin hole is to be situated within the tolerance field H7.


#### More information

#### **Notes**

Knurling pitch and knurling depth may differ from DIN.

## **Drawing**






picture 1

picture 2

# **Order information**

Dimensions									Suitable	I	Art. No.
d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d₄	d₅ Predrilled	е	h	k	t	straight pin DIN 7	_	
[mm]										[9]	
with pin hole, form B – picture 2, Stainless steel											
M10	36	28	30	2.9	4	20	14	8	3,0 m6 x 28	86	24480.0310

## **Application example**



## Compliance

## **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

#### Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

#### **Does not contain Proposition 65 substances**

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

#### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Halder France SAS

www.halder.fr Page 2 of 2

Published on: 8.4.2024