# Torque Handles 24710.0508



# **Product Description**

Torque handles are used wherever a limitation of the exerted hand force is required. The handle, similar to a knurled nut / knurled thumb screw, with integrated torque mechanism allows a defined torque limit during tightening. Reaching the torque results in an "over-locking". For releasing the torque is transmitted indefinitely.

These handles combine the functionality of a ratchet wrench with the modern and ergonomic design of a nurled nut / knurled thumb screw.

# **Material**

#### Cap

 Thermoplastic PA 6, light grey, similar to RAL 7035

# Torque mechanism

• Steel, hardened

#### Handle

· Aluminium, black anodised

# Inner part

· Steel, blackened

### Screw


· Steel, blackened


#### More information


# **Further products**

• Three-Lobed Torque Handles










picture 2

picture 1



# **Order information**

Dimensions							J	Tightening torque +/- 10%	Ă	Art. No.
d <sub>1</sub>	d <sub>3</sub>		d4	d₅	h₁	h <sub>2</sub>	max.	max.		
[mm]							[°C]	[Nm]	[g]	
with screw – picture 2										
52	M12	50	19	32	54	15.5	100	3	270	24710.0508

# Compliance

# **RoHS compliant**

Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w Contains lead - SVHC list [REACH] as of 23.01.2024.

# **Contains Proposition 65 substances**

# 

Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

# Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.