Tapered Shaft Hubs • with lock nut, stainless steel

25050.0330



Product Description

It is a self-centering and non-floating tapered shaft hub in corrosion-protected design with a hexagon nut and a lock nut.

The rotational accuracy of the tapered shaft hubs is 0,03 mm.

By using tapered shaft hubs, all shaft-hub joints of machine elements such as sprocket wheels, gear wheels, belt pulleys, cams, levers etc. can be easily and efficiently established.

Material

External part

· Stainless steel, nickel-plated

Inner part

· Stainless steel, nickel-plated

Nut

· Stainless steel, nickel-plated, hardened

Assembly


The lock nut at the outer part facilitates locking of the shaft-hub joint if freely rotating shafts are involved. For mounting, a cresent wrench (thickness max. l_2 - l_3) is used.

More information

References

Comply with mounting instructions, mounting examples, and technical data.

Drawing



Order information

Dimensions					ws	Tightening	Transferable	Transferable	Surface	Surface	Hub bore	Shaft diameter	I	Art. No.
d₁	d ₂	l ₁	l ₂	l ₃		torque of	torque	axial load	pressure	pressure	D ₁	D ₂	_	
	_		_			the nut	М	F _a	of shaft	of hub	H9	h9		
						TA	max.	max.	p _W	p _N				
						max.			max.	max.				
	[mm]			[mm]	[Nm]	[Nm]	[kN]	[N/mm²]	[N/mm ²]	[mm]	[mm]	[g]		
30	42	44	33	23	50	249	423.5	28.3	113	123	42	30	341	25050.0330

Accessories

special fork wrench	WS [mm]	[9]	Art. No.
	50	870	25050.0850



Halder France SAS www.halder.fr Page 1

Compliance

RoHS compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Halder France SAS www.halder.fr Page 2 of 2

Published on: 4.2.2024