# Height-Adjusting Elements ⋅ high 25120.0114



## **Product Description**


For levelling of machines and installations.


For vertical adjustment, the self-locking height-adjusting elements are fitted with a fine-pitch thread. All elements have a throughgoing bore for fastening purposes. A turn-out lock serves as height limit for the maximum adjustment height.

#### Material

· Heat-treated steel, zinc-plated by galvanization, chromalized

## Drawing





## **Order information**

Dimensions					Stroke	For screw	Load capacity	Load capacity	I	Art. No.
d₁	d <sub>2</sub>	$d_3$	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>		for static load	max.	_	
			~	~	~		max.			
[mm]				[mm]	[mm]	[kN]	[kN]	[g]		
9	32	M20 x 1	35	55	20	M8	65	48	152	25120.0114


#### **Accessories**

	For height adjusting element size $d_2$	Dimensions of sickle spanner DIN 1810, form A	i	Art. No.							
	[mm]	[mm]	[g]								
sickle spanner for vertical adjustment											
	32	30 – 32	46	25120.0982							



Halder France SAS www.halder.fr Page 1 of 2

### **Application example**



### Compliance

#### **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

#### Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

## Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Halder France SAS www.halder.fr Page 2 of 2
Published on: 4.2.2024