Rubber Endstop Buffers • low structure

25150 1132



Product Description

For elastic, damping, and noise-reducing bearings. They also protect the surfaces. The rubber endstop buffers can also be used as spacers and foot ends. Hardness is 70 $\pm 5^{\circ}$ Shore A.

Material


Support washer

Steel, zinc-plated by galvanization, passivated


Body

NBR

Drawing









picture 2

Order information

d ₁						Spring rate R	Load capacity max.	Spring range	min.	max.	ı	Art. No.
[mm]						[N/mm]	[N]	[mm]	[°C]		[g]	
with through-bore – picture 1												
32	4	5	9	2	1.1	1680	1680	1	-30	120	12	25150.1132

Application example







Compliance

RoHS compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 23.01.2024.

Contains Proposition 65 substances



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Halder France SAS www.halder.fr Page 2 of 2 Published on: 4.2.2024